

PRODUCT SPECIFICATION SHEET



Portable Cold Water Electric Pressure Washer

The **Cyclone portable pressure washers** are a commercial-grade, cold water pressure washer built in-house by [Tri-Mech Inc.](#) Designed to efficiently flush away caked-on dirt, mud, and heavy debris, this unit delivers high-performance cleaning ideal for agricultural, commercial, and industrial applications. This unit uses a manual on/ off switch and is recommended to turn off if not using for more than 5 minutes.

Standard Equipment & Accessories Included

- **High-Pressure Hose:** 50 feet of premium high-pressure hose.
- **Spray Gun:** Industrial-grade insulated trigger gun assembly.
- **Lance / Wand:** Heavy-duty chrome lance with nozzle.

Key Features & Benefits

- **Auto Start / Timed Off Automation:** Prevents heat build-up inside the pump by timing out the motor when the gun is not in use. This protects the seals and avoids catastrophic pump failure from continuous bypass running.
- **High Flow Efficiency:** Blending 2000 to 3000 PSI with a high 4GPM up to 5GPM flow rate ensures rapid flushing action, cutting cleaning times down significantly.
- **Rugged Portability:** Mounted on a heavy-duty stainless steel frame designed to easily move across farms, shops, and job sites.

Cyclone Pressure Washer Warranty

- **Coverage Period:** Warranty coverage is for a period of one year on all major components.
- **Operating Conditions:** All warranty coverage is subject to proper installation and usage of equipment as indicated in the installation instructions.
- **Shop Claims:** All warranty claims cover parts and labor at our service shop..
- **On-Site Claims:** For on-site warranty claims, parts and labor are covered for actual time spent on repair, however road time and service call will be charged.
- **Wear Parts Exclusion:** Please note that parts that are considered to be wear parts will not be covered.
 - *Excluded Wear Items Include:* Belts; check valves; chemical injectors; fuel filters; high pressure discharge hose; nozzles; O-rings; quick couplers; packings and seals on wet-end of pump; oil seals, lights, gaskets; trigger guns, wands; water strainers & filters.

Manufacturer Information & Support

This Cyclone unit is supported directly by **Tri-Mech Inc.**, 7877 Wellington Rd 8, Drayton, Ontario, N0G1P0

- **Phone Number:** (519) 638-2836



Technical Specifications

Model Number	PCW4-2000A	PCW5-3000A/ AB	GCW5-3000B
Water Temperature	120°F Max Recommended	120°F Max Recommended	120°F Max Recommended
Mobility Configuration	Portable (Stainless Steel Wheeled Cart Design)	Portable (Stainless Steel Wheeled Cart Design)	Portable (Stainless Steel Wheeled Cart Design)
Drive	Direct	Direct or Belt	Belt
Motor Power	5 HP	10 HP	Honda GX390
Voltage	208-240V/ 575V	208-240V/ 575V	N/A
Phase	Single or 3 phase	Single or 3 phase	N/A
Amperage	21 AMP	41 AMP	N/A
Max Fuse	30 AMP	50 AMP	N/A
Maximum Pressure	2000 PSI	3000 PSI	3000 PSI
Flow Rate	4 GPM	5 GPM	5 GPM
Control System	Auto Start / Timed Off (Smart Delay)	Auto Start / Timed Off (Smart Delay)	N/A
Dimensions	36"Lx22"Wx35"H.	41"Lx26"Wx35"H.	36"Lx22"Wx35"H.
Weight	180 LB approx.	290 LB approx.	160 LB approx.

